

LONG-LASTING, FUEL-EFFICIENT TRACTION.

Introducing a premium, multi-faceted drive tire that's as uncompromising as it is reliable. With its specialized compound and unique tread elements, the 709ZL™ delivers the optimum balance of fuel economy, treadwear and traction, making it the ideal choice for long-haul applications.

LASTING PERFORMANCE



Tie-bar Connectors

Increase block rigidity and reduce heel-toe wear for greater stability, while Z-blocks create multiple biting edges, providing aggressive, best-in-class snow traction without sacrificing treadwear.



Circumferential Grooves


Expel water, providing better tread-to-surface contact and uncompromising wet weather performance.

TREAD COMPONENTS DESIGNED TO ENHANCE FUEL ECONOMY



26/32" Tread Depth

Minimizes tread block movement for stability on the road and maximum fuel efficiency.



Zenvironment Compound

Leverages a unique single-stage mixing process for more evenly dispersed molecular elements, resulting in a longer lasting tread and lower rolling resistance for better fuel economy.

MAXIMUM DURABILITY FOR UNMATCHED RELIABILITY



Zenvironment Casing

Helps distribute contact pressure more evenly across the tread surface, resulting in long, even wear—so long, it's backed by a 7-year warranty.



Finite Element Method

Results in a casing designed to withstand natural growth delivering a tire that's both more durable and more retreadable.

IT'S IN OUR DNA.



Our innovative business philosophy, SmartSolution®, is our commitment to meeting the most essential demands of today's fleets: Longevity, Efficiency, Availability and Dependability.



Zenvironment® engineering reduces fuel consumption, waste and pollution by utilizing advanced construction and manufacturing.

SmartWay® Verified

Our 709ZL is one of many Yokohama tires designed to meet SmartWay's stringent low rolling resistance criteria.



SIZES AND SPECIFICATIONS

TIRE SIZE	PART NUMBER	PLY RATING (L.R.)	TIRE WEIGHT (LBS)	RIM SIZE (INCH)		INFLATED DIMENSIONS		TREAD DEPTH (1/32")	LOADED DIMENSIONS		RPM	MAX LOAD CAPACITY AT COLD INFLATION PRESSURE				MAX SPEED (MPH)
				MEASURE	ALT	OVERALL WIDTH (INCH)	OVERALL DIAMETER (INCH)		SECTION WIDTH (INCH)	STATIC RADIUS (INCH)		LB/PSI SINGLE	LB/PSI DUAL	KG/KPA SINGLE	KG/KPA DUAL	
295/75R22.5	70901	14G	125.0	9.00	8.25	11.6	40.6	26	12.6	18.9	514	6175@110	5675@110	2800@760	2575@760	75
11R22.5	70902	14G	130.2	8.25	7.50	11.0	41.9	26	12.1	19.5	497	6175@105	5840@105	2800@720	2650@720	75
285/75R24.5	70903	14G	129.4	8.25	--	11.1	41.8	26	12.0	19.6	498	6175@110	5675@110	2800@760	2575@760	75
11R24.5	70904	14G	137.0	8.25	7.50	11.0	43.9	26	12.1	20.5	473	6610@105	6005@105	3000@720	2725@720	75

Yokohama tires are subject to an ongoing development process. Yokohama Tire Corporation reserves the right to change product specifications at any time without notice or obligation. Not all models and sizes available in all locations.

THE YOKOHAMA DIFFERENCE

When you do business with us, you get more than just a world-class tire engineered by some of the industry's best. You also get a partner, committed to delivering efficient products and solutions to help your business run more smoothly and more profitably. Our industry-leading support network truly makes Yokohama the SmartSolution.



SMARTSOLUTION CERTIFIED PROGRAM

Each of the dealers that make up our expansive nationwide service network is selected and certified to ensure they're ready to provide the solutions you need, fast.



YOKOHAMA EMERGENCY SERVICE (YES)

Offering nationwide emergency service we're focused on keeping your cargo on the move—24/7/365.



YOKOHAMA IS A SMARTWAY TRANSPORT PARTNER

Working with the SmartWay program we're committed to accelerating the availability, adoption and market penetration of advanced fuel efficient technologies and operational practices in the freight supply chain helping you save fuel, lower costs and reduce adverse environmental impact.

Yokohama Tire Corporation | 800.423.4544 | yokohamatruck.com

Commercial Customer Service: ext. 2889

Credit Department: ext. 3977

Consumer Affairs: ext. 2880

Commercial Customer Service Dealer Order Fax: 800.455.9656